80x80x38mm JA8038



- **Motor:** Two-pole shaded pole induction motor
- **Frame :** Aluminum Alloy，Painted black
- **Impeller :** Retardant thermoplastic in black color，rated UL94V-0
- **Speed Range :** ±10%
- **Impedance Protected**

SPECIFICATIONS

Model	Bearing	Operating Voltage (V)	Frequenzy (Hz)	Air Flow (CFM)	Static Pressure (mmH_2O)	Rated Speedy (R.P.M)	Rated Current (Amp)	Rated Power (Watt)	Noise (dBA)	Weight (g)
JA8038HB1	Dual Ball	110-120	50/60	28/32	3.7/5.0	2400/2800	0.17/0.13	13/11	30/34	280
JA8038MB1	Dual Ball		50/60	22/26	2.8/4.5	2200/2600	0.15/0.12	12/10	27/30	
JA8038HS1	Sleeve		50/60	28/32	3.7/5.0	2400/2800	0.17/0.13	13/11	30/34	
JA8038MS1	Sleeve		50/60	22/26	2.8/4.5	2200/2600	0.15/0.12	12/10	27/30	
JA8038HB2	Dual Ball	220-240	50/60	28/32	3.7/5.0	2400/2800	0.07/0.06	10/8	30/34	
JA8038MB2	Dual Ball		50/60	22/26	2.8/4.5	2200/2600	0.06/0.05	9/7	27/30	
JA8038HS2	Sleeve		50/60	28/32	3.7/5.0	2400/2800	0.07/0.06	10/8	30/34	
JA8038MS2	Sleeve		50/60	22/26	2.8/4.5	2200/2600	0.06/0.05	9/7	27/30	

Should none of our standard parameters meet your requirements, please feel free to contact us, We are ready to develop custom-tailored products exclusively for you.



